

BCS Series

Electronic Crane Scales



- **Superb Quality**– Aluminium-casting case, high firm hook and shackle. GB/T11883-2002 and European CE directives
- **Strong Reliability**– Cutting edge technology, quality integrated circuit for high performance and long time stability
- **Three Popular Capacities**–
1000 kg / 2000 lb
3000 kg / 6000 lb
5000 kg / 10,000 lb
- **Visible LED Display**– Adjustable brightness for any environment
- **Dual Power**– Internal rechargeable battery or AC power
- **Remote Control**– Offers increased safety and convenience
- **Auto-Off Function**– Can be set from 0 to 60 minutes

VALUE IN
WEIGHING

BCS Series Electronic Crane Scales

Features

Brecknell crane scales are versatile, economic solutions for overhead material handling and weighing applications.

Remote Control: Puts all scale functions at your fingertips


Elongated Upper Shackle: Accommodates thick hooks

Swivel Hook with Latch: Makes load connection easy and secure

Bright LED Display: Has three adjustable brightness levels for any environment

Dual Units of Measure: Displays kg or lb

Accumulator Function: Calculates total weight



| Model | A | B | C | L | Weight |
|----------|-------|--------|-------|--------|---------|
| BCS-1000 | 68 mm | 112 mm | 40 mm | 420 mm | 11 kg |
| BCS-3000 | 68 mm | 112 mm | 40 mm | 420 mm | 11 kg |
| BCS-5000 | 68 mm | 112 mm | 45 mm | 450 mm | 12.5 kg |

Part Number:

816965006618: 2000 lb / 1000 kg

816965006625: 6000 lb / 3000 kg

816965006632: 10,000 lb / 5000 kg

R.D. Jacobs Company
500 Southeast Thirteenth Street
Fort Lauderdale, Florida 33316
Phone: 954.462.1932
Fax: 954.527.4466
email: info@dynamometers.com



a division of Avery Weigh-Tronix, LLC



Specifications

Capacities: 1000 kg x 0.5 kg / 2000 lb x 1 lb
3000 kg x 1 kg / 6000 lb x 2 lb
5000 kg x 2 kg / 10,000 lb x 5 lb

Accuracy: +/- 0.1% of full scale

Factory Calibration: 39° latitude optimized

Dimension: 255 mm (L) x 210 mm (W) x 440 mm (D)
10" L x 8" W x 17" H

Power: 7.2VDC power adapter, 1000mA with central positive and 6V/4.0Ah lead acid rechargeable battery (both included)

AWT05-508541 - UK power adapter

AWT05-508542 - EU power adapter

AWT05-508543 - US power adapter

Option:

Remote: AWT05-503633

Typical Battery Life: Depending on LED brightness and idle mode setting, battery works from 60 hrs to 200 hrs

Charging Time: Approximately 12 hrs; red LED charging, green finished

Display: 35 mm / 1.4" ultra-bright LED

Remote Functions: Zero, tare, hold, acc, del F1, F2, off, 2nd

Remote Distance: Maximum 10 m / 32'

Tare Range: 100% F.S.

Zero Range: 4% F.S.

Stable Time: ≤10 sec

Overload: 100% F.S. + 9 divisions

Overload Indication: Internal counter at +9 divisions F.S.

Ultimate Safety Factor: 400% F.S.

Safety Load: 150% F.S. of capacity

Operating Temperature: -10° C to 40° C / 14° F to 104° F

Operating Humidity: 20° C ≤90%

Shipping Weight: 12.65 kg / 27.88 lb

Packaging Dimension:

600 mm (L) x 270 mm (W) x 310 mm (H)

23" L x 10" W x 12" H

Accuracy Class: GB/T 11883-2002 Class III

Agency Approvals: CE, EC Machinery Directive

